


Rescue HTF

Heat Transfer Cleaner Concentrate



Heat Transfer Fluids

Rescue HTF is an advanced formulation consisting of premium, fast-acting concentrated cleaners. It is designed to be added to existing fluid to remove carbon, varnish and other hydrocarbon-related deposits. Maintaining system cleanliness will help ensure consistent performance and prevent reductions in efficiency related to fouling.

Rescue HTF is recommended for use at a ratio of 10% cleaner to heat transfer fluid. Heavily fouled systems may require increased concentration up to 20%.* Do not exceed a system temperature of 65°C (149°F) when using Rescue HTF.


Applications

- Heavily fouled systems
- Restoration of idled systems

Performance Advantages

- Ideal for heavily fouled systems
- Cleans while system is in operation
- Concentrated performance
Maximum cleaning at low mixing ratios
- Easy disposal
Can be disposed using standard oil recycling services
- Quickly remove varnish and sludge deposits from heat exchangers
- Improves batch times and reduces energy consumption

Temperature Range



Typical Properties	Rescue HTF
Minimum Temperature, °C (°F)	-40 (-40)
Maximum Bulk Temperature, °C (°F)	65 (149)
Flash Point °C (°F)	96 (205)



5266 Highway Avenue
Jacksonville, FL 32254
USA

toll-free: 1-800-503-9533
phone: 904-378-3232
fax: 904-378-9696

email: sales@iselinc.com
web: www.calderafluids.com

*Contact an Isel representative for the correct ratio for your application. Fluid properties are typical results and should not serve as a sole resource for determining the correct fluid for a particular application. Please consult an Isel representative to ensure that the product is the correct choice for the application. Revised 9/2018 - M